

Visa Tap2Phone Testing



- Customer can only do application debug testing by themselves; ASTA agreement with Visa Approval Services (Visa Partner Portal (<https://partner.visa.com/>)).
- Cross testing is NOT required since June, 26, 2021.
- LOC: Letter of Conformity is possible – testing requirement is only functional testing of the kernel.
- Customer submits at least one sample.
- Based on the Tap2Phone requirement, the signature must be supported and DRL should not be supported.
- Change interval for test plan is random; at the moment the VRTPKS test plan is valid.
- Reader Controller (RC) is optional. If no RC is supported, 136 config files must be provided by the customer.
- Available tool in Lab from ICC Solutions
- Customer fills out Tap2Phone ICS/ Questionnaire → Send directly to Visa Approval Services → Visa approves ICS and sends testing authorization to lab
- Lab can start testing before testing authorization (Only for Tap2Phone).
- The checksum must be specified in the ICS and cannot be changed. Otherwise, the customer has to resubmit the ICS to VISA. Please make sure that the 2nd submission must be the final one. Visa does not allow 3rd and 4th submission of questionnaires for Tap2Phone products.
- After the start of the TA test (type approval) NO CHANGE is allowed, otherwise we have to restart.
- Full TA run, including performance testing, takes 3~4 days(including report).
- After TA session, lab will provide a report to the customer → Customer must accept that the lab can send the results/report to Visa
- Customer is responsible for providing the user manual for RC and apk approval period: 3 years and no renewal.